Domestic Friction Hinges

For use on uPVC, timber or aluminium windows

Specification

- Standard friction hinges suitable for domestic applications.
- Available in : 8” to 20” for top hung windows.
  : 8” to 24” for side hung windows.
- Manufactured from stainless steel; austenitic (201)
- The nylon sliding shoe with adjustable screw offers controlled friction for smooth operation.
- Hinge opens both ways

Domestic Friction Hinge SS201

		channel info(mm)		stack height	Opening Angle	Material	**Price per Pair**
	size(inch)	bars	bar width				
Top Hung							
	8"	4 bars	16mm	17	60°	ss201	**POA**
	10"	4 bars	16mm	17	30°	ss201	**POA**
	16"	4bars	16mm	17	65°	ss201	**POA**
	20"	4bars	16mm	17	65°	ss201	**POA**
Side Hung							
	8"	4 bars	16mm	17	60°	ss201	**POA**
	12"	4bars	16mm	17	87°	ss201	**POA**
	16"	4bars	16mm	17	87°	ss201	**POA**
Heavy Duty	24"	6bars	16mm	17	87°	ss201	**POA**

ri

Minimum order 1 box. Packing 30/40/50 pairs per box (depending on size). Hinges open both ways.

Tel/Fax: 01909 269698
Mob: 07887 993829

email: enquiries@wt-hardware.com
web: www.wt-hardware.com

Registered Office: 102 Union St
Harthill, Sheffield, S26 7YH